


Langostino Lay/Bury Submersible



Simultaneous lay/bury operations for subsea pipelines

The LANGOSTINO is a self propelled pipeline trenching machine designed to bury up to 48" pipeline down to 3' below mudline. Multiple passes can acheive up to a 16' trench while the machine uses it's up to a 16' trench while the machine uses it's jetting capabilities to cut through the toughest clay. While cutting, the LANGOSTINO's airlifts are used to lift the material away from the trench. The LANGOSTINO technology can be used be used as a stand-alone operation from lay barges, four-point vessels, liftboats and DP vessels. The LANGOSTINO has proven itself in the Gulf of Mexico as an efficant and economical means for burying any length of pipeline.

Systems Onboard Include:

□ Structural

Frame designed for stability with three certified padeyes for lifting and setting.

- ☐ Hydraulic
 - 4 hourglass rollers centered under the machine track down the pipeline.
- □ Air

4 airlifts mounted on the machine lift cuttings away from the ditch.

□ Water

Ajustable jetting nozzles along with 3,000gpm@ 900psi jet pumps give ample cutting capcity.

Specifications Length 198" Width 7'10" **Dry Weight** 16,755 lbs. Submerged Weight 7,716 lbs. **Operating Depth** 20' to 300' **Buoyancy Control** Ballast 4 Tank Compensation Attitude & Current **Trenching Equipment 6 Rotating Cutting** Heads Nozzles (per head) (4-8)**Ridge Busters** 2 stems (optional) **Propulsion** Self-Propelled 1 set Hydraulic Fore 1 set Hydraulic Aft **Jump External Fixtures** Rollers Speed 700/hr PERSPECTIVE VIEW

Pipelay Minimum 24" 58" O.D. Maximum Control Hose Bundle 600' **Attached** Rear of Lay Vessel Hydraulic Type Cutting Depth (Single) 3'to Top of Pipe 10' to Top of Pipe Depth (Tandem) Air Venturis Parapet Avoidance To Surface Dispersement **Air Compressors** (Qty 12-3) 600 CFM 80-120 psi **TOP VIEW**

LL&G Construction, Inc. 110 Industrial Blvd. Houma, LA 70363 Helyn Ledet

985-851-1141 (office) 985-791-8209 (cell)